

E
3000
3040
3045
3055
3060



POWER, SIMPLICITY AND EFFICIENCY.

Thanks to the E 3000 G series of isodiametric four-wheel drive tractors, ARBOS provides an efficient answer to operators who need an easily handled, agile and stable machine for work on slopes and where there's not much space for manoeuvring. The E 3000 G series includes tractors with power ratings that range from 25 to 38 hp produced in with steering (SW) wheels and the articulated (AR) version, suitable when an even tighter turning radius is required.

- +** EXCELLENT PRICE/PERFORMANCE RATIO
- +** THE "ENTRY LEVEL" TRACTOR
- +** STEERING AND ARTICULATED
- +** LOWERED, SPACIOUS AND ERGONOMIC COCKPIT



		E			
		3030 G SW	3040 G SW	3045 G SW	3045 G AR
Type		Diesel			
Power rating	kW(hp)	19 (25)	25 (33)	28 (38)	
Nominal rate	rpm	2800			
N° Cylinders	n°	2 natural aspiration		3 aspirated	
Cooling		Air		Water	
Swept volume	cc	1248		1649	
Tank capacity	lt	24			30
N° Speeds		9 speeds: 6 forward + 3 reverse			
Main clutch		6" diameter dry clutch			
Front differential lock		Mechanical system, with manual locking through independent levers			
Rear differential lock		Mechanical system, with manual locking through independent levers			Mechanical system, with manual locking through pedal
Speed	Kph	30			
Type of brakes		Rear brakes, drum type. Mechanical control. Independent or simultaneous braking and integral on the 4 wheels			
Type of steering		Hydraulic, hydrostatic type			
Steering angle		45°			30°
Type		Independent at 540 rpm and synchronized with all gears	Independent at 540/750 rpm and synchronized with gearbox speeds		
Clutch		Dry disc type			
Control		Mechanical			
Type		Floating Up and Down Lifter			
Lifting capacity	Kg	1000			1200
3 point hitch		Class 1			Class 1 and 1N
Pump flow rate	lt/min	18,5	25		
Rear hydraulic control valves		Max 1, double acting			
Safety frame		Folding roll bar			
Instruments		Analog	Digital		
Driver's seat		Adjustable both in horizontal and vertical position mounted on elastic, homologated suspension			
Tow hook		Class B			
		SW	SW	SW	AR
Length	mm	2870	3005	3005	2660
Width min. and max.	mm	1103 - 1203	1103 - 1203	1110 - 1431	1000 - 1290
Height to safety frame	mm	1970	1970	2000	2005
Wheelbase	mm	1155	1155	1155	1294
Front track min. and max.	mm	896 - 996	896 - 996	1010 - 1200	742 - 1288
Rear track min. and max.	mm	896 - 996	896 - 996	1010 - 1200	742 - 1288
Weight with safety frame	Kg	1100	1100	1350	1300
Front - Rear (Standard)		7,50x16"		8,25x16"	8,25x16"
		29x12,50"Garden	29x12,50"Garden - 260/70-16"	-	-

ENGINE

TRANSMISSION

BRAKES AND STEERING

REAR PTO

REAR POWER LIFT

HYDRAULIC CIRCUIT

DRIVER'S AREA

WEIGHTS AND DIMENSIONS

TYRES

Optional

* Tyres considered 7.50x16" (E 3000 G 30 SW - 40 SW) and 8.25x16" (E 3000 G 45 SW - 45 AR)